

LED SPOT Light

GELite



BL-MR16-4XPE



BL-GU10-4XPE



BL-AR111-9 SEMI

fin housing

| Item Number | BL-AR111-7SEMI | BL-MR16-3XPE | BL-GU10-3XPE | BL-MR16-4XPE | BL-GU10-4XPE | BL-AR111-9SEMI |
|--------------------------|------------------------|------------------------|---------------------------|------------------------|---------------------------|------------------------|
| Voltage | 12V AC/DC | 12~24V AC/DC | 85~145V AC 190~265V AC | 12~24V AC/DC | 85~145V AC 190~265V AC | 12~24V AC/DC |
| Lumens | WW: 590lm CW: 760lm | WW: 270lm CW: 360lm | WW: 270lm CW: 360lm | WW: 290lm CW: 390lm | WW: 290lm CW: 390lm | WW: 610lm CW: 775lm |
| Dimmable | YES | YES | YES | YES | YES | YES |
| Dimension | Ø111x55mm | Ø50x55mm | Ø50x60mm | Ø50x55mm | Ø50x60mm | Ø111x55mm |
| Available Base | AR111 | MR16 | GU10/E26/E27 | MR16 | GU10/E26/E27 | AR111 |
| Weight | 450g | 40g | 55g | 40g | 55g | 450g |
| LED Type/ QTY | SEMI / 7pcs | CREE XPE/ 3pcs | CREE XPE/ 3pcs | CREE XPE/ 4pcs | CREE XPE/ 4pcs | SEMI/ 9pcs |
| Power Consumption | 9.0W | 5.8W | 5.8W | 5.8W | 5.8W | 15.0W |

General Specs:

CCT: 2,700~7,000K, CRI: Ra>80, PF>0.9, Beam Angle: 15,25,45 degree